


SERIES AURORA

Recessed aluminum profile for indirect lighting

Once recessed in your walls and ceilings, this series with an exceptional look will allow you to put the accent wherever you want with great style and incomparable visual comfort. Like most LED123 products, it comes with many color, finish, wattage, lens and assembly options. Favoring better heat dissipation despite being embedded, this series will stand out for its uncompromising performance.



Description	mm	Inch
A - Width flange	68.00	2.6772
B - Width interior	10.20	0.4016
C - Width exterior	58.00	2.2835
D - Height	14.00	0.5512



FEATURES

- Indirect lighting
- Stylish
- Recessed
- Can be cut according to your needs
- Allows continuous joint mounting
- Wide choice of lens
- Wide choice of colors and finishes
- Clear Anodized Aluminum 6063T5

MOUNTING



PROJECTION

Indirect




APPLICATION

- Steps
- Regular (all purpose)

POWER

Type	Lumen Meter	Feet	Watt Meter	Feet
Unique white	420	128	4.8	1.5
Unique white	500	152	4.8	1.5
Unique white	840	256	9.6	2.9
Unique white	1000	305	9.6	2.9
Unique white	700	213	12.0	3.7
Unique white	1100	335	12.0	3.7
Unique white	1400	427	14.0	4.3
Unique white	1200	366	14.4	4.4
Unique white	1700	518	18.0	5.5
Unique white	1700	518	19.2	5.9
Unique white	1800	549	19.2	5.9
Unique white	4000	1219	22.0	6.7
Variable white	750	229	9.6	2.9
Variable white	1500	457	19.2	5.9
Variable white	1680	512	19.2	5.9
Variable white	1500	457	23.0	7.0
Variable white	2000	610	23.0	7.0
Dim to warm	1800	549	23.0	7.0
RGB			8.5	2.6
RGB			14.4	4.4
RGB			17.0	5.2
RGB			20.0	6.1
RGB			20.0	6.1

COLOR TEMPERATURE

Kelvin	Type
2200K	 RGB
2400K	
2700K	
3000K	 Dim to warm 1800K - 3000K
3500K	
4000K	 Variable white 2500K - 6000K 2700K - 6000K
5000K	
5200K	
6000K	
6500K	

GRADATION

Type
Not dimmable
Dimmable Triac
Dimmable 0-10 Volt

DIFFUSER

Type	Light diffuse	Angle
Opalin	78 %	120 °
Frost	85 %	120 °
Clear	93 %	120 °

SHAPE



LUMINAIRE COLOR





Sale sheet

31-08-2021 09:58:06

DISCLAIMER

Due to our continued efforts to improve our documents and products, the specifications found on this document are subject to change without notice.