


SERIES LIBERALIS

Recessed aluminum profile with narrow flanges

Once recessed, this series, with its narrow trim (border), will integrate perfectly with your decor and will allow you to put the accent where you want it and in style. Like most LED123 products, it comes with many colors, finishes, wattage, lenses and assembly options. Favoring better heat dissipation despite being recessed, this series will stand out for its uncompromising performance.



Description	mm	Inch
A - Width flange	30.50	1.2008
B - Width interior	18.70	0.7362
C - Width exterior	23.50	0.9252
D - Height	11.50	0.4528




FEATURES

- Modern and discreet
- Stylish
- Can be cut to your needs
- Allows continuous joint mounting
- Direct lighting
- Wide choice of lens
- Wide choice of colors and finishes
- Clear Anodized Aluminum 6063T5

MOUNTING



PROJECTION




APPLICATION

Regular (all purpose)

POWER

Type	Lumen Meter	Feet	Watt Meter	Feet
Unique white	420	128	4.8	1.5
Unique white	500	152	4.8	1.5
Unique white	840	256	9.6	2.9
Unique white	1000	305	9.6	2.9
Unique white	700	213	12.0	3.7
Unique white	1100	335	12.0	3.7
Unique white	1400	427	14.0	4.3
Unique white	1200	366	14.4	4.4
Variable white	750	229	9.6	2.9
RGB			8.5	2.6
RGB			14.4	4.4

COLOR TEMPERATURE

Kelvin	Type
 2200K	 RGB
 2400K	
 2700K	 Variable white 2500K - 6000K
 3000K	
 3500K	
 4000K	
 5000K	
 5200K	
 6000K	
 6500K	


GRADATION

Type
Not dimmable
Dimmable Triac
Dimmable 0-10 Volt

DIFFUSER

Type	Light diffuse	Angle
Opalin	78 %	120 °
Frost	85 %	120 °
Clear	93 %	120 °

SHAPE



LUMINAIRE COLOR





Sale sheet

31-08-2021 09:52:59

DISCLAIMER

Due to our continued efforts to improve our documents and products, the specifications found on this document are subject to change without notice.