

FLX-28.8-20MM-3528-24

LED flexible strip



FEATURES


- Various angles 120 °
- With self-adhesive tape on the back
- Made up of high quality LEDs
- Work voltage DC24V
- Cut every 49.21mm

APPLICATIONS

- Car decoration
- Architectural decorative lighting
- Archway, ceiling, bridge edge lighting
- Auditorium walkway lighting
- Signage letters backlighting
- Channel letter lighting


MECHANICAL SPECIFICATIONS

-Dimensions version 240DEL/m



Unit: mm
Cut: 49.21mm

-Connection diagram



- ① Power supply (driver)
- ② LED strips
- ③ Wires

TECHNICAL SPECIFICATIONS


LED DIMENSIONS



SMD3528
(3.5mm x 2.8mm)



240DEL/m
dual line



Cut every
49.21mm



24 volt

POWER



28.8W/m



20mm

PCB WIDTH

COLOR



Warm white:
2700/3000K, 2000-2200lm/m

Nature white:
4000-4500K, 2200-2300lm/m

Pure white:
6000-6500K, 2300-2400lm/m

PROTECTION TYPE



IP20

NOTICE

Before application, please make sure the power supply is in accordance to the strips.

DISCLAIMER

Due to our continued efforts to improve our documents and products, the specifications found on this document are subject to change without notice.