

FLX-12-8MM-3528-24

LED flexible strip



FEATURES


- Various angles 120 °
- With self-adhesive tape on the back
- Made up of high quality LEDs
- Work voltage DC24V
- Cut every 25.4mm

APPLICATIONS

- Car decoration
- Architectural decorative lighting
- Archway, ceiling, bridge edge lighting
- Auditorium walkway lighting
- Signage letters backlighting
- Channel letter lighting

MECHANICAL SPECIFICATIONS


-Dimensions version 240DEL/m



Unité: mm
Coupe: 25.4mm



-Connection diagram



- ① Power supply (driver)
- ② LED strips
- ③ Wires

TECHNICAL SPECIFICATIONS

LED DIMENSIONS




SMD3528
(3.5mm x 2.8mm)

LED QTY



240DEL/m

INCREMENT



Cut every
25.4mm

VOLTAGE



24 volt

POWER



12W/m

PCB WIDTH



8mm

COLOR



Warm white:
2700-3500K, 850-950lm/m

Nature white:
4000-4500K, 950-1050lm/m

Blanc pur:
5000-6000K, 1050-1150lm/m

PROTECTION TYPE



IP67

NOTICE

Before application, please make sure the power supply is in accordance to the strips.

DISCLAIMER

Due to our continued efforts to improve our documents and products, the specifications found on this document are subject to change without notice.